

## How to Safely Relight a Grill

- 1. Turn off the gas and open the grill lid.
- 2. Check instructions from the manufacturer on when it is safe to relight the grill.
- 3. Leave the gas off and leave the grill top open for 5 minutes.
- 4. Never lean over a grill when lighting or cooking.

For more on guidelines regarding proper handling of a propane cylinder for your gas grill and the proper sequence for starting your gas grill go to: http://www.blossmangas.com/content/propane/safety.

## **RV and Propane Safety**

- 1. Clear any debris from exterior vents: sticks, dust, twigs, insects, or other items that may restrict venting.
- 2. Check propane cylinders for wear and tear. Check exterior vents and inspect propane cylinders and holding mechanisms for any signs of rust, corrosion, or fatigue.
- 3. Inspect all propane appliance connections for frays and damage.
- 4. Make sure your RV has a Class BC fire extinguisher and propane detectors. If you need to replace or install a new detector, be sure to follow the manufacturer's instructions regarding installation, location and maintenance.
- 5. Have your vehicle inspected annually.

Whether renting or buying a new or used vehicle, RV users should look for a blue BC Safety Authority decal confirming that a certified technician has completed a comprehensive propane system safety inspection and has made the necessary repairs.

You can receive a free brochure "Propane and Your Recreational Vehicle" from the Propane Research Educational Council (PERC) <u>http://www.allianceautogas.com/wp-</u> content/uploads/2014/06/RV propane-brochure1.pdf